

TRIAC BT floor welding set




Linoleum and PVC floor welding made easy

- Light and easy to handle
- Ergonomic handle for welding without strain
- Electronically protected heating element
- Integral precision nozzle
- Built-in start up protection in case of power interruption
- Complete kit including accessories tool box and spare heating element



SPECIFICATIONS




136.936

Voltage	V~	230
Power consumption	W	1600
Temperature	°C	20 – 700
Air flow (20°C)	l/min	230
Noise emission level LpA	dB	67
Size (L x W x H)	mm	370 × 90, handle 56Ø
Weight	kg	1.0
Marking of conformity		
Approval mark		
Certification scheme		CCA, CB
Protection class II		

136.940

Voltage	V~	120
Power consumption	W	1550
Temperature	°C	20 – 700
Air flow (20°C)	l/min	230

Plastic Welding > Hand tools > TRIAC BT floor welding set

Noise emission level LpA	dB	67
Size (L x W x H)	mm	370 × 90, handle 56Ø
Weight	kg	1.0
Marking of conformity		
Approval mark		
Certification scheme		CCA, CB
Protection class II		

ACCESSORIES



Speed welding nozzle 4.5 x 12mm for fillet seams

107.139 - Speed welding nozzle 4.5 x 12mm for fillet seams, push-fit on tubular nozzle Ø 5mm



Speed welding nozzle 3, 4, 5 mm push-fit on tubular nozzle Ø 5 mm

106.989 - Speed welding nozzle 3 mm, push-fit on tubular nozzle Ø 5 mm

106.990 - Speed welding nozzle 4 mm push-fit, on tubular nozzle Ø 5 mm

106.991 - Speed welding nozzle 5 mm, push-fit on tubular nozzle Ø 5 mm




Spatula

106.969 - Spatula



Heating element 136.916

136.916 - Heating element 136.916



Tool box 116.586

116.586 - Tool box